


# Ficha Técnica Perfil HEA



H= Altura      T= Espesor del ala      S= Espesor del alma

B= Base      R= Ángulo

Elaborados bajo la norma ASTM - A36 / EN 10025-2-S27JR+AR

PERFIL HEA	Dimensiones (mm)					ÁREA (cm <sup>2</sup> )	PESO (Kg/m)	Momento respecto a los ejes					
	H (mm)	B (mm)	S (mm)	T (mm)	R (mm)			EJE-X-X			EJE-Y-Y		
								Ix cm <sup>4</sup>	Sx cm <sup>3</sup>	Rx cm	Iy cm <sup>4</sup>	Sy cm <sup>3</sup>	Ry cm
100	96	100	5.0	8.0	12	21.2	16.7	349	72.7	4.05	134	26.7	2.51
120	114	120	5.0	8.0	12	25.3	19.9	606	106.0	4.89	231	38.4	3.02
140	133	140	5.5	8.5	12	31.4	27.7	1030	155.0	5.73	389	55.6	3.52
160	152	160	6.0	9.0	15	38.8	30.4	1670	220.0	6.57	615	76.9	3.98
180	171	180	6.0	9.5	15	45.3	35.5	2510	294.0	7.45	924	103.0	4.52
200	190	200	6.5	10.0	18	53.8	42.3	3690	389.0	8.28	1330	133.0	4.98
220	210	220	7.0	11.0	18	64.3	50.5	5410	515.0	9.17	1950	178.0	5.51
240	230	240	7.5	12.0	21	76.8	60.3	7760	675.0	10.10	2770	231.0	6.00
260	250	260	7.5	12.5	24	86.8	68.2	0500	836.0	11.00	3660	282.0	6.50
280	270	280	8.0	13.0	24	97.3	76.4	13700	1010.0	11.90	4760	340.0	7.00
300	290	300	8.5	14.0	27	113.0	88.3	18300	1260.0	12.70	6310	420.0	7.49
320	310	300	9.0	15.5	27	124.0	97.6	22900	1480.0	13.60	6980	465.0	7.49
340	330	300	9.5	16.5	27	133.0	105.0	27700	1680.0	14.40	7430	495.0	7.46
360	350	300	10.0	17.5	27	143.0	112.0	33100	1890.0	15.20	7880	525.0	7.43
400	390	300	11.0	19.0	27	159.0	125.0	45100	2310.0	16.80	8560	571.0	7.34
450	440	300	11.5	21.0	27	178.0	140.0	63700	2900.0	18.90	9460	631.0	7.29
500	490	300	12.0	23.0	27	198.0	155.0	87000	3550.0	21.00	10400	691.0	7.24
550	540	300	12.5	24.0	27	212.0	166.0	112000	4150.0	23.00	10800	721.0	7.15
600	590	300	13.0	25.0	27	226.0	178.0	141000	4790.0	25.00	11300	751.0	7.05
650	640	300	13.5	26.0	27	242.0	190.0	175000	5470.0	26.90	11700	781.0	6.96
700	690	300	14.5	27.0	27	260.0	204.0	215000	6240.0	28.70	12200	812.0	6.84
800	790	300	15.0	28.0	30	286.0	224.0	303000	7680.0	32.60	12600	842.0	6.65
900	890	300	16.0	30.0	30	321.0	252.0	422000	9480.0	36.30	13500	903.0	6.50
1000	990	300	16.5	31.0	30	347.0	272.0	554000	11200.0	40.00	14000	933.0	6.35